

Dräger REGARD® 3900 Control System

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.



Benefits

Flexible design

The Regard 3900 can be equipped with up to four 4 - 20 mA input cards. Each input card can be connected to up to four gas detectors, either 2 or 3 wire, giving a maximum of 16 gas detectors per each Regard 3900. Each input module is equipped with three alarm relays.

These relays are designated as common alarms for the corresponding input card for "Fault", "1st alarm" and "2nd alarm". The 1st and 2nd alarm relays are fully configurable and can be set up as rising or falling and latching or non-latching.

In addition, the Regard 3900 can be equipped with up to two relay modules. Each relay module has eight additional relays.

In accordance with the ATEX directive, the first relay is always configured as a fault relay and cannot be changed. The other seven relays can be configured as individual, common or voting alarms. They can either operate as normally open or normally closed relays.

The alarm relays are acknowledged by operating a button at the front of the control unit.

Quick and easy configuration

The Config 3900 configuration software enables quick and easy configuration via a laptop or a PC. With new installations, the configuration can initially be carried out online and then loaded during commissioning. During maintenance the system configuration can be downloaded from the device to a PC for checking. The appropriate connection cable and the required software are available as accessories.

Robust enclosure

The robust IP65 enclosure enables the installation of the control system at virtually any location within a safe area.

System components



ST-11859-2007

Dräger PIR 7000

The Dräger PIR 7000 is an explosion proof point infrared gas detector for continuous monitoring of flammable gases and vapours. With its stainless steel SS 316L enclosure and drift-free optics this detector is built for the harshest industrial environments, e.g. offshore installations.



ST-3812-2003

Dräger Polytron® 7000

The Dräger Polytron® 7000 is a gas detector that can satisfy all toxic and oxygen gas measurement applications on a single platform. It is meeting the requirements of the compliance market as well as the high specification requirements of customized solutions.



D-11158-2011

Dräger PEX 3000

The transmitter Dräger PEX 3000 detects flammable gases and vapors in concentrations below their Lower Explosion Limit. Its DD-sensor provides a very long-term stable measuring signal and responds to gas in only a few seconds.



ST-3800-2005

Dräger Polytron® 7500

The Dräger Polytron® 7500 is a gas detector for nitrogen trifluoride (NF₃), fluorinated and chlorinated hydrocarbons in ambient air.

System components



D-49077-2012

Dräger Flame 5000

The Dräger Flame 5000 is an explosion proof colour imaging based flame detector. Each detector operates standalone and incorporates, within a single unit, an integrated CCTV system; digital signal processing and software algorithms to process live video image and interpret the characteristics of a flame.

Related Products



2-669-95

Dräger REGARD® control system

Tried and tested thousands of times and infinitely flexible. The modular Regard® control system can be individually adapted to any monitoring task. Suitable for SIL 2 systems, the Regard® system is also ATEX approved, and meets EMC directive standards.



ST-335-2004

Dräger REGARD-1

The Dräger REGARD-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron SE Ex measuring head.

Related Products



2-928-95

Dräger QuadGuard

The Dräger QuadGuard is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The system can be configured for up to four independent gas detectors.

Technical Data

Type	Control unit for location in a non-hazardous area	
Gas and ranges	Toxic, oxygen and combustible gases with user definable measuring ranges. Refer to transmitter type for ranges, name and engineering units. All configurations by Laptop computer.	
Inputs	2 or 3 wire 4-20 mA transmitters Remote reset 24 VDC supply	
Outputs	Alarm 1, Alarm 2 and Fault as standard Warning and Inhibit relays on optional relay board Single, common or voted alarms on optional relay board Acknowledgeable relays on optional relay board Repeat 4-20 mA via optional Repeat Board	
Display	4 line, 40 character back-lit LCD Active, Fault, Alarm 1 and Alarm 2 LED's per input DC and AC power LED's Inhibit LED	
Power supply	External	24 VDC, or
	Internal	2.5 A, 5 A or 10 A power supply @ 110/240 VAC
Dimensions (approx.)	420 x 300 x 190 mm / 16.5" x 11.8" x 7.5" (W x H x D)	
Weight (approx.)	3 kg / 6.6 lbs, depending upon installed power supply	
Ambient conditions	Temperature	0 to 55 °C / 32 to 130 °F
	Pressure	700 to 1300 hPa / 20.6 to 38.3 inch Hg
	Humidity	0 to 100 %RH, non condensing
Ingress Protection	IP 65, ABS – OV material of construction	
Approvals	ATEX	II (2)G Acc. to Directive 94/9/EC
	CE-mark	Electromagnetic compatibility (directive 89/336/EEC) Low voltage directive (72/23/EEC, 93/68/EEC)

Ordering Information

Dräger REGARD 3900 Basic Unit	42 08 780
Dräger REGARD 3900 4-20 Module	42 08 782
Dräger REGARD 3900 Relay Module	42 08 784
Dräger REGARD 3900 RS232 Interface	42 08 785
Dräger REGARD 3900 4-20mA Repeat Output Board	42 08 797

Notes

Notes

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

SYSTEM CENTERS

P. R. CHINA
Dräger Safety Equipment
(China) Co., Ltd.
A22 Yu An Rd, B Area,
Tianzhu Airport Industrial Zone,
Shunyi District,
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

GERMANY

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck
Tel +49 451 882-2794
Fax +49 451 882-4991

UNITED KINGDOM

Dräger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 544 475

REGION EUROPE SOUTH

Dräger Safety France SAS
25, rue Georges Besse
92182 Antony Cedex, France
Tel +33 1 46 11 56 00
Fax +33 1 40 96 97 20
Europe.South@draeger.com

USA

Dräger Safety, Inc.
505 Julie Rivers, Suite 150
Sugar Land, TX 77478
Tel +1 281 498 1082
Fax +1 281 498 5190
info.gds@draeger.com

REGION ASIA PACIFIC

Dräger Safety Asia Pte Ltd
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama Comercial
S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

Locate your Regional
Sales Representative at:
www.draeger.com/contact

